

Installing the Absorgel Hanging 1kg

The Absorgel Hanging 1kg is an extremely versatile desiccant. A hook and the presence of grommets allow you to place the units either vertically or horizontally to best suit the configuration of your cargo.



Horizontal Installation



Vertical Installation

Vertical Installation

- 1** Remove the Absorgel Hanging from the transparent PE film (Note the unit immediately is activated.) Be careful not to cut into the Absorgel.
- 2** In most cases, the small piece of the hook needs to be twisted off and attached to the unit. Place the Absorgel Hanging Hook on to the container walls' lashing ring. The hook should lock into place with a click.
- 3** Let the unit hang, then remove the strips on the rear of the Absorgel Hanging unit to expose the adhesive backing. Press firmly against the container to secure into place. Note a cable tie through the units grommets can also be used for additional security.



Pro-Ex exclusive distributor of Absortech products



Horizontal Installation

- 1** Activate the Absorgel Hanging by opening the transparent outer protective plastic and taking out the unit. Be careful not to cut into the Absorgel.
- 2** Put a nylon string (or cable tie) through one of the grommets of the Absorgel.
- 3** Tighten the nylon string (or cable tie) around the container lashing ring.
- 4** Repeat steps 2 and 3 above for securing the Absorgel through the other grommet.



Disposal Absorgel Hanging is a single-use product and can be disposed as regular waste. The calcium chloride and gelling agent are non-toxic and the polyethylene (PE) and polypropylene (PE) plastics are recyclable.

Safety The calcium chloride brine is non-toxic and non-corrosive. It is similar to very salty seawater. In case of contact flush eyes with fresh water. Rinse exposed areas of skin with fresh water. Pro-Ex recommend using gloves and goggles when handling.

Pro-Ex exclusive distributor of Absortech products

