PRO EX
PROTECTION EXPERTS
AUSTRALIA

Product Specification Sheet:

SKU	SD-1G
Product name	Silica gel desiccant 1g (Bead size:2-4mm)
Edge cutting mode	Flat cut
Packing paper	Aihua paper
Seal	Back seal
Product size	20*40mm±2mm
Carton size	37*27.5*24.5cm
Packing details	1400pcs/bag, 5 bags/carton

Description: Silica gel is a transparent spheroidal particle. The main component is SiO-2. Because of the large surface area, silica gel has a high moisture absorption rate. Silica gel can be reactivated without affecting its moisture absorption capacity. It is therefore very economical, easy to dispose and environment-friendly.

Technical Specification:

Item/ condition		Standard
Moisture Content (180 ℃) %		≤3.0%
Moisture Absorption Capacity (T=25±2 ℃)	RH=20±2%	≥9.5%
	RH=50±2%	≥22.0%
	RH=90±2%	≥33.0%
PH		4~8
Specific Resistance		≥3000Ω.cm
Granularity Percent of Pass%		≥90%
Bulk Density g/L		≥750

Silica gel desiccant must always be kept in airtight containers to avoid moisture.

The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

Protection Experts
P.O.Box 2143
Normanhurst NSW 2076

Tel : 02 994 50593
Email : sales@pro-ex.com.au
Website : www.pro-ex.com.au
ABN # 41654089120